

Pallet Rack

IDEAL STORAGE FOR PALLETIZED ITEMS

Fully welded, roll-formed uprights with a teardrop design provide a greater strength-to-weight ratio. Upright structures are 100% MIG welded with precision K-brace and heavy-duty cross channel reinforcement for increased strength.

Roll-formed beams feature an integrated 1-5/8" step for decking and are completely enclosed for clean applications. Each beam has at least three studs to engage the tapered teardrop slots in the upright with a compression fit. Beams can be adjusted on 2" vertical centers. An integral safety lock automatically locks into place when the beam is properly seated.

Pallet rack uprights conform to the latest standards set by Rack Manufacturers' Institute LRFD Specifications.



UNITS INCLUDE

- Starters Include 2 Uprights
- Add-ons Include 1 Upright
- 2 Beams per Level
- Front-to-Back Supports
OR Wire Decking Panels

- Lake Green Uprights
- Safety Orange Beams



Upright



Beam



Front-to-Back Support



Wire Decking

Width	Depth	Height	Levels	With Front-To-Back Supports		With Wire Decking		Capacity per Level
				Starter	Add-on	Starter	Add-on	
96"	42"	96"	2	RSSFB096042096	RSAFB096042096	RSSWD096042096	RSAWD096042096	5,200 lbs
	48"			RSSFB096048096	RSAFB096048096	RSSWD096048096	RSAWD096048096	
	42"	144"	3	RSSFB096042144	RSAFB096042144	RSSWD096042144	RSAWD096042144	
	48"			RSSFB096048144	RSAFB096048144	RSSWD096048144	RSAWD096048144	
108"	42"	96"	2	RSSFB108042096	RSAFB108042096	RSSWD108042096	RSAWD108042096	6,320 lbs
	48"			RSSFB108048096	RSAFB108048096	RSSWD108048096	RSAWD108048096	
	42"	144"	3	RSSFB108042144	RSAFB108042144	RSSWD108042144	RSAWD108042144	
	48"			RSSFB108048144	RSAFB108048144	RSSWD108048144	RSAWD108048144	
120"	42"	96"	2	RSSFB120042096	RSAFB120042096	RSSWD120042096	RSAWD120042096	6,140 lbs
	48"			RSSFB120048096	RSAFB120048096	RSSWD120048096	RSAWD120048096	
	42"	144"	3	RSSFB120042144	RSAFB120042144	RSSWD120042144	RSAWD120042144	
	48"			RSSFB120048144	RSAFB120048144	RSSWD120048144	RSAWD120048144	
144"	42"	96"	2	RSSFB144042096	RSAFB144042096	RSSWD144042096	RSAWD144042096	6,790 lbs
	48"			RSSFB144048096	RSAFB144048096	RSSWD144048096	RSAWD144048096	
	42"	144"	3	RSSFB144042144	RSAFB144042144	RSSWD144042144	RSAWD144042144	
	48"			RSSFB144048144	RSAFB144048144	RSSWD144048144	RSAWD144048144	